

SURFACE MOUNT ALUMINUM ELECTROLYTIC CAPACITORS

ZC Height 5.5mmL, Low Impedance Series



RC → ZC
Low Imp.

- Chip type, low impedance temperature range up to 105°C
- Designed for surface mounting on high density PC board
- Applicable to automatic insertion machine using carrier tape
- Complied to the RoHS directive

Item	Characteristics										
Operating temperature range	-55 ~ +105°C										
Leakage current max.	$I = 0.01CV$ or $3\mu A$ whichever is greater (after 2 minutes)										
Capacitance tolerance	$\pm 20\%$ at 120Hz, 20°C										
Dissipation factor max. (at 120Hz, 20°C)	WV	6.3	10	16	25	35					
	$\tan\delta$	0.22	0.19	0.16	0.14	0.12					
Low temperature characteristics (Impedance ratio at 120Hz)	WV	6.3	10	16	25	35					
	Z-25°C/Z+20°C	2	2	2	2	3					
	Z-55°C/Z+20°C	4	4	3	3	3					
Load life (after application of the rated voltage for 1000 hours at 105°C)	Leakage current	Less than specified value									
	Capacitance change	Within $\pm 20\%$ of initial value									
	$\tan\delta$	Less than 200% of specified value									
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and $\tan\delta$ are same as load life value. The measurement shall be performed at 20°C by the KS C IEC 60384 - 4										
Resistance to soldering heat	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them at 250°C for 10 seconds.										
	Leakage current	Less than specified value									
	Capacitance change	Within $\pm 10\%$ of initial value									
	$\tan\delta$	Less than specified value									

● DRAWING (See page 55)

Unit : mm

-Series code of ZC is "Z"

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF	WV	6.3			10			16			25			35		
1.0														4×5.3	5.0	50
1.5														4×5.3	5.0	50
2.2														4×5.3	5.0	50
3.3														4×5.3	5.0	50
4.7														4×5.3	5.0	50
6.8														4×5.3	5.0	80
10								4×5.3	5.0	50	5×5.3	2.6	80	5×5.3	2.6	80
15								5×5.3	2.6	80	6.3×5.3	1.3	75	6.3×5.3	1.3	115
22	4×5.3	5.0	50	5×5.3	2.6	80	5×5.3	2.6	80	6.3×5.3	1.3	115	6.3×5.3	1.3	115	
33	5×5.3	2.6	80	5×5.3	2.6	80	6.3×5.3	1.3	115	6.3×5.3	1.3	115				
47	5×5.3	2.6	80	6.3×5.3	1.3	115	6.3×5.3	1.3	115							
68	6.3×5.3	1.3	115	6.3×5.3	1.3	115										
100	6.3×5.3	1.3	115													

Ripple current (mA rms) at 105°C, 100kHz
Impedance (Ω) at 20°C, 100kHz
Case size $\varnothing D \times L$ (mm)

● FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz
Coefficient	0.35	0.5	0.64	0.83	1.00